GISB / HTTP Header – Best Practice

(**Boldface** indicates required elements.)

```
POST /gisb/servlet/InboundHTTP HTTP/1.0
Accept: multipart/form-data, */*
Accept-Language: en-us
TE: trailers
Expect: 100-continue
Host: 123.45.678.910:80
Connection: Keep-Alive
User-Agent: myBatchBrowser/1.0
Date: Wed, 18 Dec 2001 02:22:00 CST
Authorization: Basic fT8erD+4w==
Content-Length: 34344
Content-Type: multipart/form-data;boundary="-------34567933439092

-------34567933439092
Content-Disposition: form-data; name="from"

123456789
-------34567933439092
Content-Disposition: form-data; name="to"

987654321
-------34567933439092
Content-Disposition: form-data; name="input-format"

X12
-------34567933439092
Content-Disposition: form-data; name="input-data";filename="c:\f1.dat"
Content-Type: application/octet-stream

qANQr1DbwE4f8Ki4uiwe45Dder3kDbwE4f8Ki4uiwe45Dder3kqAN                    w
E4fDbwE4f8Ki4uiwe45Dder3kqANQr1DbwE4fDbwE4f8Ki4uiwe45                    f
DbwE4f8Ki4uiwe45Dder3kqANQr1DbwE4fDbwE4f8Ki4uiwe45Dder3kqANQr1DbwE4fDbw
E4f8Ki4uiwe45Dder3kqANQr1DbwE4fDbwE4f8Ki4uiwe45Dder3kqANQr1DbwE4fDbwE4f
8Ki4uiwe45Dder3kqANQr1DbwE4fDbwE4f8Ki4uiwe45Dder3kqANQr1DbwE4fDbwE4f8Ki
4uiwe45Dder3kqANQr1DbwE4fDbwE4f8Ki4uiwe45Dder3kqANQr1DbwE4fDbwE4f8Ki4ui
we45Dder3kqANQr1DbwE4fDbwE4f8Ki4uiwe45Dder3kqANQr1DbwE4fDbwE4f8Ki4uiwe4
5Dder3kqANQr1DbwE4fDbwE4f8Ki4uiwe45Dder3kqANQr1DbwE4fDbwE4f8Ki4uiwe45Dd
er3kqANQr1DbwE4fDbwE4f8Ki4uiwe45Dder3kqANQr1DbwE4fDbwE4f8Ki4uiwe45Dder3
kqANQr1DbwE4fDbwE4f8Ki4uiwe45Dder3kqANQr1DbwE4fDbwE4f8Ki4uiwe45Dder3kqA
NQr1DbwE4fDbwE4f8Ki4uiwe45Dder3kqANQr1DbwEDbwE4f8Ki4uiwe45Dder3kqAN
-------34567933439092--
```